



**SEMI-STEEL RADIAL TIRE
CATALOGUE**



SHANDONG TERAFLEX TYRE CO., LTD

PAGE

ABOUT US

01	COMPANY PROFILE
02	CERTIFICATE
03	EQUIPENT
04	R&D CENTER

PRODUCT DIRECTORY

05	ECORUN 101
07	ECORUN 102
09	PRIMACY 201
11	PRIMACY 202
13	GRANDPOWER A/T
15	CITYCROSS H/T
17	SUPERTRAC 301
19	SUPERTRAC 302
21	POLAR BEAR

COMPANY PROFILE >>>

SHANDONG TERAFLEX TYRE CO., LTD. Established in November 2015, is a experienced and reliable tyre supplier in Qingdao city, Shandong China, offering Passenger car tyres, light truck tyres, 4x4 tyres, truck and bus tyres etc.

Wide range, satisfied quality, stable supply, competitive price.

Annual production capacity is 1.5 million pieces for PCR and 1 million pieces for TBR. At the same time, we research and develop the variety of special products according to the market demand and customer needs.



CERTIFICATE >>>



EQUIPMENT >>>




EQUIPMENT >>>





HIGH PERFORMANCE


ECORUN 101



Four grooves with open shoulder provides perfect water evacuation.



Center rib design delivers better straight handling.



Improved shoulder sipes provide better handling during cornering and noise emission.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WINTH (mm)	OVERALL DIAMETER (mm)	MAXLOAD KG LBS	MAX PRESSURE Kpa Psi	UTQG
155/65R13	73	T	41/2J	157	532	365/805	350/51	360 AA
155/70R13	75	T	4.50B	157	548	387/853	350/51	360 AA
155/80R13	79	T	4.50B	157	578	437/963	350/51	360 AA
165/65R13	77	T	5J	170	544	412/908	350/51	360 AA
165/70R13	79	T	5.00B	170	562	437/963	350/51	360 AA
175/70R13	82	T	5.00B	177	576	475/1047	350/51	360 AA
185/70R13	86	T	51/2J	189	590	530/1168	350/51	360 AA
155/65R14	75	T	41/2J	157	558	387/853	350/51	360 AA
165/60R14	75	H	5J	170	554	387/853	350/51	360 AA
165/65R14	79	H	5J	170	570	437/963	300/44	360 AA
165/70R14	81	T	5J	170	588	462/1018	350/51	360 AA
175/65R14	82	H	5J	177	584	475/1047	350/51	360 AA
175/70R14	84	T	5J	177	602	500/1102	350/51	360 AA
185/60R14	82	H	51/2J	189	578	475/1047	350/51	360 AA
185/65R14	86	H	51/2J	189	596	530/1168	350/51	360 AA
185/70R14	88	T	51/2J	189	616	560/1235	350/51	360 AA
195/60R14	86	H	6J	201	590	530/1168	350/51	360 AA
195/70R14	91	T	6J	201	630	615/1356	350/51	360 AA
205/60R14	88	H	6J	209	602	560/1235	300/44	360 AA
205/70R14	95	H	6J	209	644	690/1521	350/51	360 AA
215/70R14	96	H	61/2J	221	658	700/1565	350/51	360 AA
175/65R15	84	H	5J	177	609	500/1102	350/51	360 AA
185/60R15	84	H	51/2J	189	603	500/1102	350/51	360 AA
185/65R15	88	H	51/2J	189	621	560/1235	350/51	360 AA
195/50R15	82	V	6J	201	577	475/1047	350/51	360 AA
195/55R15	85	V	6J	201	595	515/1135	350/51	360 AA
195/60R15	88	H	6J	201	615	560/1235	350/51	360 AA
195/65R15	91	H	6J	201	635	615/1356	350/51	360 AA
205/60R15	91	H	6J	209	627	615/1356	350/51	360 AA
205/65R15	94	H	6J	209	647	670/1477	350/51	360 AA
205/70R15	96	T	6J	209	669	710/1565	350/51	360 AA
215/70R15	98	T	61/2J	221	683	750/1653	350/51	360 AA
225/70R15	100	H	61/2J	228	697	800/1764	300/44	360 AA
205/45R16	83	H	7J	206	590	487/1073	350/51	360 AA
205/55R16	91	V	61/2J	214	632	615/1356	350/51	360 AA
205/60R16	92	H	6J	209	652	630/1389	350/51	360 AA
215/55R16	93	V	7J	226	642	650/1433	350/51	360 AA
215/60R16	95	H	61/2J	221	664	690/1521	350/51	360 AA
225/50R16	92	V	7J	233	632	630/1389	350/51	360 AA
225/55R16	95	V	7J	233	654	690/1521	350/51	360 AA
225/60R16	98	H	61/2J	228	676	750/1653	350/51	360 AA






ECORUN 102



Special compound design ensures a long mileage.



The combination of blocks provides a superior driving performance and a strong grip.



Three main grooves contribute to better water drainage and wet traction.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WINTH (mm)	OVERALL DIAMETER (mm)	MAXLOAD KG LBS	MAX PRESSURE Kpa Psi	UTQG
175/70R14	84	T	5J	177	602	500/1102	300/44	600 AA
185/60R14	82	H	5.5J	189	578	475/1047	300/44	600 AA
185/65R15	88	H	5.5J	189	621	560/1235	300/44	600 AA
195/60R14	86	H	6J	201	590	530/1168	300/44	600 AA
205/65R15	94	H	6J	209	647	670/1477	300/44	600 AA

